

# FLOOR STRIPPING & WAXING

## Emulso Strip


- 1** Dilute 12 to 16 oz. per gallon of Emulso Strip to very hot water into a bucket.
- 2** Flood the floor with the mixed solution. Allow it to sit on the floor for at least 5 minutes.
- 3** Scrub briskly using a floor scrubber with a stripping pad. Loosen tough areas with a doodle bug or manual-use abrasive pad.
- 4** Mop or vacuum up the solution. Rinse thoroughly with clean hot water, neutral cleaner or cup of vinegar in a bucket of water.
- 5** Repeat steps 1-4 if needed.
- 6** Allow the floor to dry completely before adding any floor finish.



## Everglo

### Distinctive Acrylic Metal Interlock Floor Finish 20% Solids

- 1** Make sure floor is properly stripped, neutralized, cleaned, and totally dry.
- 2** Line a mop bucket with a trash liner and pour in Everglo floor finish. Soak new mop head into wax so that it is completely saturated. Wring mop lightly.
- 3** Working in manageable sections drawing mop with finish along the sides of the area that you are finishing.
- 4** Fill the remainder of the section using a back and forth or figure 8 motion.
- 5** Make sure first coat is dry before applying each additional coat. Repeat steps 3 and 4 until complete.



## HELPFUL HINTS:

1. Always use a clean mop head.
2. Line the mop bucket with a trash liner to eliminate bucket cleaning after waxing.
3. Apply coats lightly. 2 light coats are better than one heavy coat.
4. Rayon mop heads work better for applying finish.
5. At least 3 light coats are recommended for best results.